

FUSO — A Daimler Group Brand



2017

FG4X4

Efficiency that delivers.



MITSUBISHI FUSO TRUCK OF AMERICA, INC.

FG4X4

SPECIFICATIONS

When the going gets tough, take your business where it needs to go in the industry's only four-wheel drive cabover – the FUSO FG4X4. At the press of a button, experience extra traction and solid climbing ability, whether on rugged terrain, slippery roads, or snow-covered streets. Featuring an innovative two-stage turbocharged, low-emissions diesel engine and dual-clutch automatic transmission, you'll benefit from increased fuel savings, enhanced efficiencies, higher payload capacity, and improved driver productivity. Add to this our 5-year/175,000-mile powertrain limited warranty and you get the longevity and durability you can expect from FUSO.



WEIGHT RATINGS	GVWR/GCWR	14,050 lb./21,765 lb.
	GAWR (front/rear)	5,730 lb./9,480 lb.
	Base model	5,995 lb. (est.)
CURB WEIGHT	Base model	5,995 lb. (est.)
BODY/PAYLOAD	Estimated max.	8,055 lb. (see dealer for details)
DIMENSIONS	Wheelbase	134.4" (E)
	Overall length (cab/chassis)	228.5"
	Usable cab to rear axle	104.8"
	Body sizes accommodated	13' to 15'
	Model	FUSO 4P10-T5 Diesel
ENGINE	Type	DOHC, 4-cylinder, 4-stroke cycle, water-cooled, turbocharged, intercooled diesel with 4 valves per cylinder, with high-efficiency electrically-engaged cooling fan
	Displacement/Emissions	183 cu. in. (3.0 L) Electronically controlled DPF/SCR system with OBD
	Max. output (SAE, gross)	161 hp @ 3,400 rpm
	Max. torque (SAE, gross)	295 lb.-ft. @ 1,300 rpm
	Type	Dry paper element with snorkel
AIR CLEANER	Type	Dry paper element with snorkel
TRANSMISSION	Standard equipment	M038S6 DUONIC® 6-speed dual-clutch AT, transfer case with push-button controlled, electro-vacuum activated 4-wheel drive
AXLE CAPACITY	Front/Rear	6,175 lb./9,480 lb.
FINAL REDUCTION GEAR	Type	Single-reduction hypoid, limited-slip (rear)
	Ratio (std./opt.)	5.285/5.714
TOP SPEED, EST.	Std. diff./Opt. diff.	86/80 mph
TURNING DIAMETER	Minimum, by wheelbase	44.2'
TIRES (PREMIUM)	Configuration	Single front, dual rear
	Size/Type	235/85R16 10PR LR:E, traction, all positions
WHEELS	Size/Configuration	16" x 6"/6-lug, free-wheeling/lockable front hubs
STEERING	Type	Ball-nut type with integral-type hydraulic power boost
	Adjustments	Tilt/telescoping steering column with steering lock
SUSPENSION	Front	Laminated leaf springs with shock absorbers
	Rear	Laminated leaf springs with shock absorbers
BRAKES	Service	Drum, vacuum/hydraulic-type with ABS
	Parking	Drum/driveline, internal expanding shoe
	Exhaust	Electrically actuated
FRAME	Type	Ladder/drop/tapered
	Section modulus	8.15 cu. in. per rail
	Yield strength	44,235 psi
	RBM per rail	360,300 lb.-in.
	Height/Width	35.8"/29.6"
	Environmental durability	Premium anti-corrosion package for frame and frame-mounted components
FUEL TANK	Capacity/Location	33 gal./left side
DEF TANK	Capacity/Location	3.2 gal./right side
BATTERY	Type/Capacity	Two 12-volt, maintenance-free/750 CCA
ELECTRICAL	Starter/Alternator	12-volt/12-volt, 140A output
COLD WEATHER	Starting/Operation	Ceramic glow plugs/PCV heater, DEF tank heater
CONVENIENCE/ASSURANCE	Windows/Door locks	Power-operated, one-touch up and down driver's side window
	Cruise control	Standard (programmable)
	Entry	Keyless, with driver/assistant door lock control
	Radio	Clarion AM/FM/CD, hands-free Bluetooth® (optional)
	Air conditioning	Standard factory-installed
	Idle Limit System (ILS)—opt.	Automatic engine shutdown of stationary vehicle, in Park or Neutral, after achieving normal operating temperature with dealer-programmed limit of 3, 5 or 10 minutes
	Collision avoidance system	Mobileye® 6 Series (optional)

KEY BENEFITS

- Go where your competition can't with locking front hubs, heavy-duty axles, all-terrain tires, and 9 in. of ground clearance
- A push-button operated all-wheel-drive system makes it easy to select between efficient rear-wheel-drive and powerful all-wheel-drive
- Our exclusive DUONIC® dual-clutch automatic transmission offers effortless navigation of rugged terrain or winter driving conditions
- Enjoy the long haul in our most comfortable cab ever, fully equipped with an ergonomically designed interior, adjustable steering wheel, and spacious seating and stowage
- From sunrise to sundown, a panoramic windshield and a driver-to-ground line of sight of only 6 ft. ensure you stay focused on what's ahead
- Go further on less with our ultra-efficient advanced dual-turbo diesel engine with access to high torque whenever it's needed
- Mobileye® system provides audible and visual alerts for speeding, lane departure, potential pedestrian or vehicle collisions


¹Optional feature

CAB COLORS

ARCADIA SILVER	MARS RED
NATURAL WHITE	SHANNON BLUE
JUPITER GREEN	SOLID BLACK

All models are available immediately in white. Other colors shown (except Solid Black) may be special-ordered at no extra charge. Accuracy of indicated hues is limited by paper/electronic reproduction.

FABRIC STYLE



Vehicle specifications are subject to change without notice. Photos and descriptions included in this spec sheet may vary in comparison to actual vehicle models. Please see your local dealer for details and warranty limitations.

PRINTED IN THE U.S.A.
©2017 MITSUBISHI FUSO TRUCK OF AMERICA, INC.

MITSUBISHI FUSO TRUCK OF AMERICA, INC.

2015 Center Square Road
Logan Township, NJ 08085

MITFUSO.COM

